

Technical data

# HC 130 VIO



**Compactors Series HC**  
Compactor with VIO drum

H255

## HIGHLIGHTS

- > High compaction performance
- > VIO compaction system – vibration or oscillation
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

**TECHNICAL DATA HC 130 VIO (H255)**

**Weights**

Operating weight with cab	kg	12920
Operating weight with ROPS	kg	12800
Empty weight without cab, without ROPS	kg	11980
Max. operating weight	kg	17350
Axle load, front/rear	kg	7650/5270
Axle load at max. operating weight, front/rear	kg	8380/8970
Static linear load, front	kg/cm	35,75
French classification, value/class		
Wheel load per tyre, rear	kg	2635

**Machine dimensions**

Total length	mm	6117
Total height with cab	mm	3054
Total height with ROPS	mm	3054
Height loading, min.	mm	3054
Centre distance	mm	3266
Total width with cab	mm	2474
Maximum working width	mm	2140
Ground clearance, centre	mm	461
Kerb clearance, left/right	mm	477/477
Turning radius, inside	mm	4131
Slope angle, front/rear	°	34,2/23,7

**Drum dimensions**

Drum width, front	mm	2140
Drum diameter, front	mm	1504
Drum thickness, front	mm	20
Drum type, front		Smooth

**Tyre dimensions**

Tyre size, rear		AW 23.1-26 12 PR
Width over tyres, rear	mm	2122
Number of tyres, rear		2

**Diesel engine**

Manufacturer		JOHN DEERE
Model		JDPS 4045PTE
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		101,0/137,3/2000
Power SAE J1349, kW/HP/rpm		101,0/135,4/2000
Exhaust emission standard		EU Stage IIIA / EPA Tier 3
Exhaust emissions category		UN ECE R96 (Tier 3)
Exhaust gas after-treatment		-

**Travel drive**

Speed, infinitely variable	km/h	0 - 12,1
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	52/58

**Vibration**

Vibration frequency	Hz	33
Amplitude, vibration	mm	1,95
Centrifugal force, vibration	kN	280

**Oscillation**

Oscillation force	kN	296
Oscillation frequency	Hz	34
Tangential amplitude, oscillation	mm	1,62

**Steering**

Pendulum angle +/-	°	max. 12
Steering, type		Articulated steering

**Tank capacity/filling capacity**

Fuel tank, capacity	L	280
---------------------	---	-----

**Sound level**

Sound power level L(WA), guaranteed	db(A)	108
Sound power level L(WA), representative measurement	db(A)	106

**EQUIPMENT**

12 V sockets (2-fold) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Plastic scraper, for smooth drum

**OPTIONAL EQUIPMENT**

ROPS cab with heating and air-conditioning system (FOPS, level I) | Seat belt monitoring device | Auxiliary heater | Radio | Tachograph | Bluetooth interface for Smart Doc | Dozer blade | Padfoot shells | Vibration plate | Automatic engine stop | Camera system | JDLink | Working spotlights | Engine hood with electrical release mechanism | Coming Home function