

Technical data

# HC 250 C VC



## Compactors Series HC

Compactor with vibration crusher drum

H257

### HIGHLIGHTS

- > 2 in 1: Crushing and compacting in one process
- > High crushing force owing to high point load
- > Wide range of applications (e.g. road construction, landfill site construction, surface mining, etc.)
- > New toolholder system for simple tool changes
- > Powerful drive, no-spin axle and 3-point articulation for outstanding traction and off-road mobility

**TECHNICAL DATA HC 250 C VC (H257)**

**Weights**

Operating weight with cab	kg	24695
Max. operating weight	kg	26300
Axle load, front/rear	kg	17560/7135
Axle load at max. operating weight, front/rear	kg	18540/7760
Static linear load, front	kg/cm	82,06
French classification, value/class		-
Wheel load per tyre, rear	kg	3567,5

**Machine dimensions**

Total length	mm	6871
Total height with cab	mm	3046
Height loading, min.	mm	3046
Centre distance	mm	3553
Total width with cab	mm	2496
Maximum working width	mm	2140
Ground clearance, centre	mm	453
Kerb clearance, left/right	mm	580/580
Turning radius, inside	mm	4904
Slope angle, front/rear	°	44,6/25,7

**Drum dimensions**

Drum width, front	mm	2140
Drum diameter, front	mm	1710
Drum thickness, front	mm	35
Drum type, front		VC
Tool holder, quantity		126

**Tyre dimensions**

Tyre size, rear		EM 23.5-25/20PR TL
Width over tyres, rear	mm	2082
Number of tyres, rear		2

**Diesel engine**

Manufacturer		DEUTZ
Model		TCD 2012 L06 2V
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		150,0/203,9/2000
Power SAE J1349, kW/HP/rpm		150,0/201,2/2000
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust emissions category, EU		EU Stage IIIA
Exhaust emissions category, USA		EPA Tier 3
Exhaust gas after-treatment		-

**Travel drive**

Speed, infinitely variable	km/h	0 - 11,8
Regulation, infinitely variable		HAMMTRONIC/manual
Gradeability, with/without vibration	%	59/66

**Steering**

Steering angle +/-	°	35
Pendulum angle +/-	°	10
Steering, type		Articulated steering

**Tank capacity/filling capacity**

Fuel tank, capacity	L	336
---------------------	---	-----

**Sound level**

Sound power level L(WA), guaranteed	db(A)	107
Sound power level L(WA), representative measurement	db(A)	104

**EQUIPMENT**

12 V sockets (2-fold) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, automatic | ROPS cab with heating system (FOPS, level I) | Insert for tools

**OPTIONAL EQUIPMENT**

Seat belt monitoring device | Armrest comfort setting, left | Auxiliary heater | Radio | Tachograph | Fire extinguisher | Bluetooth interface for Smart Doc | Dashboard cover | Automatic engine stop | Camera system | Working spotlights | Rotating beacon | Engine hood with electrical release mechanism | Coming Home function | Battery isolation switch | Tool kit