

Technical data

# HD 90 P VT



## Tandem rollers Series HD

Tandem roller with vibrating roller drum and set of wheels

H296

### HIGHLIGHTS

- > 3-point articulation for even weight distribution and excellent on-centre feel
- > Ergonomic driver platform with rotatable seat operating unit and adjustable driver's seat
- > Track offset for comfortable start up, moving away and compacting at curb edges
- > Simple, intuitive and language-neutral operation
- > Excellent view of the machine and the construction site

**P**

## TECHNICAL DATA HD 90 P VT (H296)

## Weights

Operating weight with cab	kg	9010
Operating weight with ROPS	kg	8790
Empty weight without cab, without ROPS	kg	7955
Max. operating weight	kg	9670
Axle load, front/rear	kg	4770/4240
Static linear load, front	kg/cm	28,39
French classification, value/class		22,4/VX1
Wheel load per tyre, rear	kg	1060

## Machine dimensions

Total length	mm	4900
Total height with cab	mm	3010
Total height with ROPS	mm	3099
Total height with plastic protective roof	mm	3020
Height loading, min.	mm	2606
Centre distance	mm	3700
Total width with cab	mm	1807
Maximum working width	mm	1820
Ground clearance, centre	mm	340
Kerb clearance, left/right	mm	800/800
Turning radius, inside	mm	5876

## Drum dimensions

Drum width, front	mm	1680
Drum diameter, front	mm	1200
Drum thickness, front	mm	17
Drum type, front		Smooth/non-split
Track offset, left/right	mm	170

## Tyre dimensions

Tyre size, rear		11.00-20
Width over tyres, rear	mm	1620
Number of tyres, rear		4

## Diesel engine

Manufacturer		CUMMINS
Model		QSB3.9-C130-32
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		97/132/2500
Power SAE J1349, kW/HP/rpm		97/130/2500
Exhaust emission standard		UN ECE R96 (Tier 3)
Exhaust emissions category, EU		EU Stage IIIA
Exhaust emissions category, USA		EPA Tier 3
Exhaust emissions category, Brazil		MAR-I
Exhaust gas after-treatment		-

## Travel drive

Speed, infinitely variable	km/h	0 - 12,5
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	30/40

## Vibration

Vibration frequency, front, level I/II	Hz	42/50
Amplitude, front, level I/II	mm	0,62/0,34
Centrifugal force, front, level I/II	kN	75,5/59,6

## Steering

Steering angle +/-	°	30
Pendulum angle +/-	°	10
Steering, type		Articulated steering

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L	173
Water tank, capacity	L	760
Additive tank, capacity	L	22

## Sound level

Sound power level L(WA), guaranteed	db(A)	
Sound power level L(WA), representative measurement	db(A)	

## EQUIPMENT

12 V power socket | Two large exterior rear-view mirrors | Scrapers foldable | Pressure water sprinkling system | ECO mode | Driver's platform with access from both sides | Speed-controlled water sprinkling | Speed preselect | Automatic traction control and anti-slip control | Vibration-isolated driver's platform | Water-sprinkling system with spray bars front and rear | Track offset, hydraulic | Water filter system (3-fold) | Water tank front and rear, can be filled from both sides | Central water outlet | Additive-sprinkling system for tyres, rear

## OPTIONAL EQUIPMENT

Heating and air-conditioning system | | Back-up alarm | | Working spotlights | Fuel prefilter | Tool kit